

01.07 Sales and order picking containers

> Mobile containers in numerous variants and dimensions


> Bolted design for ideal material flow in intralogistics

> Push-on design for use in the sales area



ORDER PICKING CONTAINER

Basic model with accessories, bolted design
Dimensions (mm): W 1200 x D 800 x H 1635



Basic model

Basic model


Design: Sturdy, mobile chassis made of square tubing, wire bottom tray with spot-welded wire mesh. Side panels made of square tubing with welded wire grate. Two-part rear panel (closing grate). 1 connection tube at height of 1635 mm, mounted in centre. Hook-in grate can be hooked in various positions at an interval of 110 mm.

Castors (basic model): 4 Wanzl swivel castors Ø 100 mm made of polyamide, available with brakes on request. For alternative castor fittings, see accessories.


Finish: High-gloss, galvanised, chrome-plated.

Technical specifications:

Total load capacity (bolted design)	max. 500 kg
Total load capacity (push-on design)	max. 250 kg
Load capacity per shelf	75 kg



Container with height of 1100 mm, dimensions in mm



Container with height of 1635 mm, dimensions in mm

01.07 Sales and order picking containers

The right solution for every application

■ **Wanzl order picking containers** are available in a wide range of variants and dimensions. Thanks to the extensive range of accessories and the possibility of bolted or push-on design, they fit perfectly into your logistics environment and help you to pick orders more quickly and more efficiently.




ORDER PICKING CONTAINER
Basic model with accessories, bolted design
Dimensions (mm): W 1200 x D 700 x H 1100



ORDER PICKING CONTAINER
Basic model with accessories, bolted design
Dimensions (mm): W 600 x D 600 x H 1635


Bolted design

For the material flow in intralogistics, the bolted designs are ideal.



Push-on design

For use in the sales area, these mobile solutions clearly display your products in a way that promotes sales.



Noise reduction

Plastic parts for securing and noise reduction are included as standard in the scope of delivery of the hook-in grate.



Pat. pend.

5th castor (optional)

Mechanical design, simplifies steering and manoeuvring of the container. Antistatic strap as accessory.



Sales and order picking containers order numbers

Dimensions (mm)		Width 600					
Depth		600	700	800	600	700	800
Height		1100			1635		
Basic model order no. (push-on design)		06.04 440.50	06.04 432.50	06.04 431.50	06.07 668.50	06.07 705.50	06.07 734.50
Basic model order no. (bolted design)		06.00 033.50	06.00 034.50	06.00 035.50	06.00 036.50	06.00 037.50	06.00 038.50
Accessories							
	Hook-in grate straight, depth 540 mm	28.04 578.50	28.04 578.50	28.04 578.50	28.04 578.50	28.04 578.50	28.04 578.50
	Hook-in grate straight, depth 640 mm	–	28.04 441.50	28.04 441.50	–	28.04 441.50	28.04 441.50
	Hook-in grate straight, depth 740 mm	–	–	28.04 365.50	–	–	28.04 365.50
	Hook-in grate angled 25 mm, depth 540 mm	77.36 161.50	77.36 161.50	77.36 161.50	77.36 161.50	77.36 161.50	77.36 161.50
	Hook-in grate angled 25 mm, depth 640 mm	–	77.36 274.50	77.36 274.50	–	77.36 274.50	77.36 274.50
	Hook-in grate angled 25 mm, depth 740 mm	–	–	77.36 387.50	–	–	77.36 387.50
	Hook-in grate angled 100 mm, depth 540 mm	28.04 579.50	28.04 579.50	28.04 579.50	28.04 579.50	28.04 579.50	28.04 579.50
	Hook-in grate angled 100 mm, depth 640 mm	–	28.04 489.50	28.04 489.50	–	28.04 489.50	28.04 489.50
	Hook-in grate angled 100 mm, depth 740 mm	–	–	28.04 433.50	–	–	28.04 433.50
	Hook-in grate double wire edge 2 x 6.8 mm, depth 540 mm	77.37 291.50	77.37 291.50	77.37 291.50	77.37 291.50	77.37 291.50	77.37 291.50
	Hook-in grate double wire edge 2 x 6.8 mm, depth 640 mm	–	77.37 404.50	77.37 404.50	–	77.37 404.50	77.37 404.50
	Hook-in grate double wire edge 2 x 6.8 mm, depth 740 mm	–	–	77.37 517.50	–	–	77.37 517.50
	Closing grate, front Adjustable height*	06.04 529.50	06.04 529.50	06.04 529.50	06.07 102.50	06.07 102.50	06.07 102.50
	Closing grate, front Height 215 mm, for front anti-slip guard	06.08 793.50	06.08 793.50	06.08 793.50	06.08 793.50	06.08 793.50	06.08 793.50
	Scanner rail for angled hook-in grate Height 40 mm, transparent	21.71 978.07	21.71 978.07	21.71 978.07	21.71 978.07	21.71 978.07	21.71 978.07
	Horizontally fitted handle (only for bolted design!) Steel tube, plastic-coated in red, green or blue	77.38 308.76	77.38 421.76	77.38 534.76	77.38 308.76	77.38 421.76	77.38 534.76
	Vertically fitted handle (only for bolted design!) Steel tube, plastic-coated in red, green or blue	–	–	–	00.40 570.76	00.40 570.76	00.40 570.76
	Note holder W 223 x H 120 mm, made of metal, with clamping strip	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95
	Writing board W 313 x H 160 mm, coated metal board, black	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95
	Clipboard , attachable Adjustable angle, with clamping strip for formats up to DIN A4	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95
	Wire tray for small items, plastic-coated in black W 235 x D 170 x H 135 mm, mesh size 5 x 5 mm	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76
	Anti-static strap for reliable conductive discharge Mounted on chassis or on 5th castor	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95
	5th castor for castor set Ø 100 mm Simplifies steering and manoeuvring of the container	60.16 052.50	60.16 165.50	60.16 278.50	60.16 052.50	60.16 165.50	60.16 278.50
Sets of castors 100 PA (black)							
	Swivel castor set Ø 100 mm 4 swivel castors	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00
	Swivel castor set Ø 100 mm 4 swivel castors, incl. 2 with brakes	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00
Sets of castors 100 elastic (blue)							
	Swivel castor set Ø 100 mm 4 swivel castors	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00
	Swivel castor set Ø 100 mm 4 swivel castors, incl. 2 with brakes	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00

* Height adjustable ▲ Height of the closing grate of the basic model



Width 960						Width 1200					
600	700	800	600	700	800	600	700	800	600	700	800
1100			1635			1100			1635		
06.06 940.50	06.07 076.50	06.07 598.50	06.01 545.50	06.01 550.50	06.01 555.50	06.04 434.50	06.04 435.50	06.04 436.50	06.01 210.50	06.01 240.50	06.01 255.50
06.00 039.50	06.00 040.50	06.00 041.50	06.00 042.50	06.00 043.50	06.00 044.50	06.00 045.50	06.00 046.50	06.00 047.50	06.00 048.50	06.00 049.50	06.00 050.50
28.01 557.50	28.01 557.50	28.01 557.50	28.01 557.50	28.01 557.50	28.01 557.50	28.01 515.50	28.01 515.50	28.01 515.50	28.01 515.50	28.01 515.50	28.01 515.50
-	28.01 566.50	28.01 566.50	-	28.01 566.50	28.01 566.50	-	28.01 521.50	28.01 521.50	-	28.01 521.50	28.01 521.50
-	-	28.01 570.50	-	-	28.01 570.50	-	-	28.01 525.50	-	-	28.01 525.50
77.36 500.50	77.36 500.50	77.36 500.50	77.36 500.50	77.36 500.50	77.36 500.50	77.36 839.50	77.36 839.50	77.36 839.50	77.36 839.50	77.36 839.50	77.36 839.50
-	77.36 613.50	77.36 613.50	-	77.36 613.50	77.36 613.50	-	77.36 925.50	77.36 925.50	-	77.36 925.50	77.36 925.50
-	-	77.36 726.50	-	-	77.36 726.50	-	-	77.37 065.50	-	-	77.37 065.50
28.01 558.50	28.01 558.50	28.01 558.50	28.01 558.50	28.01 558.50	28.01 558.50	28.01 516.50	28.01 516.50	28.01 516.50	28.01 516.50	28.01 516.50	28.01 516.50
-	28.01 567.50	28.01 567.50	-	28.01 567.50	28.01 567.50	-	28.01 522.50	28.01 522.50	-	28.01 522.50	28.01 522.50
-	-	28.01 571.50	-	-	28.01 571.50	-	-	28.01 526.50	-	-	28.01 526.50
77.37 630.50	77.37 630.50	77.37 630.50	77.37 630.50	77.37 630.50	77.37 630.50	77.37 969.50	77.37 969.50	77.37 969.50	77.37 969.50	77.37 969.50	77.37 969.50
-	77.37 743.50	77.37 743.50	-	77.37 743.50	77.37 743.50	-	77.38 082.50	77.38 082.50	-	77.38 082.50	77.38 082.50
-	-	77.37 856.50	-	-	77.37 856.50	-	-	77.38 195.50	-	-	77.38 195.50
06.07 410.50	06.07 410.50	06.07 410.50	06.03 617.50	06.03 617.50	06.03 617.50	06.04 063.50	06.04 063.50	06.04 063.50	06.04 203.50	06.04 203.50	06.04 203.50
06.04 803.50	06.04 803.50	06.04 803.50	06.04 803.50	06.04 803.50	06.04 803.50	06.08 794.50	06.08 794.50	06.08 794.50	06.08 794.50	06.08 794.50	06.08 794.50
21.71 986.07	21.71 986.07	21.71 986.07	21.71 986.07	21.71 986.07	21.71 986.07	21.71 993.07	21.71 993.07	21.71 993.07	21.71 993.07	21.71 993.07	21.71 993.07
77.38 308.76	77.38 421.76	77.38 534.76	77.38 308.76	77.38 421.76	77.38 534.76	77.38 308.76	77.38 421.76	77.38 534.76	77.38 308.76	77.38 421.76	77.38 534.76
-	-	-	00.40 570.76	00.40 570.76	00.40 570.76	-	-	-	00.40 570.76	00.40 570.76	00.40 570.76
77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95	77.38 986.95
77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95	77.38 647.95
00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95	00.50 007.95
00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76	00.14.378.76
00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95	00.74 205.95
60.16 052.50	60.16 165.50	60.16 278.50	60.16 052.50	60.16 165.50	60.16 278.50	60.16 052.50	60.16 165.50	60.16 278.50	60.16 052.50	60.16 165.50	60.16 278.50
60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00	60.53 563.00
60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00	60.77 067.00
60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00	60.44 411.00
60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00	60.77 632.00